

Fix Tile Over Existing Tile ?

Carter-Dal CTD24 is the solution!



1. PRODUCT NAME

Carter-Dal International **CTD24** *fix tile over tile*

2. MANUFACTURER

Carter-Dal International

3. PRODUCT DESCRIPTION

Carter-Dal CTD24 fix tile over tile takes the uncertainty out of re-modelling projects. It is designed to adhere new Tile, Porcelain and Stone over existing Ceramic Tiles

Advantages

- Increased bond and compressive strength.
Interior /Exterior.
- Shock, chemical and frost resistant.
- Water resistant;
- Superior flexibility.
- Extra Heavy Service

Suitable Substrates

- Existing Tile over Cement mortar beds
- Existing Tile over Ceramic tile and stone
- Existing Tile over Concrete
- Existing Tile over Cement backer board
- Existing Tile over Cement plaster
- Existing Tile over▪ Brick masonry
- Existing Tile over Concrete masonry
- Existing Tile over Gypsum wallboard (interior walls only)

Existing Tile over Timber T&G flooring Yes it can !

Tile over uncontaminated Cement terrazzo

Packaging 5 Ltr Admix plus 20 KG bag Mortar

Limitations

Note: Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes.

Call us to talk through your project 0044(0)845-083-0117
Substrate deflections under all live, dead and impact loads, including concentrated loads, must not exceed L/360 for thin bed ceramic tile/brick installations or L/480

Tip if existing has been down for years and no signs of stress/failure, you are probably good to go, but call us first just to check.

4. INSTALLATION

Surface Preparation

All existing tiles should be between 40°F (4°C) and 90°F (32°C) and structurally sound & rigid, clean and free of all dirt, oil, grease, paint, concrete sealers or curing compounds.

Mixing

Stir Carter-Dal CDT24 Admix thoroughly before mixing with mortar powder...

Application

Mix liquid & mortar provided. Allow mortar to rest for 5–10 minutes. Adjust consistency if necessary. Remix and apply to existing tiles with a notched trowel, then apply the new tiles on to the sarration with a twisting sliding action untill fully bedded. Check alignment and level adjust to suit. Wipe surplus with a damp sponge and continue.

Coverage

Use approximately 5Lt of Carter-Dal Mortar Admix to a 20 kg of Carter-Dal mortar will cover 5M2 at a bed of 3/4 mm

5. AVAILABILITY AND COST

Where to Buy

www.carter-dal.com or call 0845-083-0117

We will put you in touch with a local stockiest

Cleaning

Mortar Clean tools and tile work with water while mortar is fresh.

6. Guarantee

Lifetime - not transferable.

7. MAINTENANC

Carter-Dal quality assured **CDT24** *fix tile over tile* construction products requiring no maintenance.

8. TECHNICAL SERVICES

Technical assistance

e-mail: Info@Carter-Dal.Com

Call: 0044(0)845-083-0113

Web www.carter-dal.com